

CONFERENCE PROCEEDINGS

The 7th International Conference on Spatial Structures and the Annual Symposium of the IASS

Edited by: Alireza Behnejad, Gerard Parke and Omidali Samavati







Table of Contents

Foreword	ii
Acknowledgements	iii
Summary of Sessions	iv
Contents	vi
Papers	1
Authors Index	

Foreword:

The present proceedings contain a collection of 330 papers on various aspects of analysis, design and construction of spatial structures such as gridshells, barrel vaults, domes, towers, retractable systems and tension structures. These papers were written by 763 authors, representing a total of 44 countries for presentation at the seventh International Conference on Spatial Structures.

The International Conference on Spatial Structures has been organised and held on five previous occasions by the Spatial Structures Research Centre of the University of Surrey in 1966, 1975, 1984, 1993 and 2002, and in 2011 in collaboration with the International Association for Bridge and Structural Engineering (IABSE) and International Association for Shell and Spatial Structures (IASS).

The seventh conference was hosted by the University of Surrey from the UK during 23rd - 27th August 2021; it was combined with the 2020 annual symposium of the IASS. The conference was named IASS 2020/21 -Surrey 7 and its strapline was "Inspiring the next generation".

The planning and delivery of the conference had a long history: beginning in January 2016, and latterly very heavily affected by the worldwide Covid 19 pandemic emerging during late 2019/early 2020. The original planned dates were 24th - 28th August 2020, but as the impact of the pandemic became more profound, the mode of delivery evolved from fully in-person, through hybrid in-person/virtual to eventually becoming fully virtual throughout the revised dates during 23rd - 27th August 2021.

The Scientific Committee was formed in May 2018 and had a membership of a hundred and twenty one leading International Engineers and Architects, from both industry and academia; representing over thirty countries. After a worldwide call for abstracts, the Scientific Committee received 468 submissions involving 1061 authors and subsequently each abstract was reviewed at least twice by members of the Committee. Feedback on the abstracts was presented to almost all of the authors and afterwards, three hundred and thirty nine full papers were received. The full papers were, in turn, reviewed by members of the Scientific Committee, who generously gave their time to provide feedback to the corresponding authors. This proceedings include contributions submitted directly by the authors and the editors cannot accept responsibility for any inaccuracies, comments and opinions contained in the text.

The editors would like to take the opportunity to thank all authors for submitting their contributions, the Scientific Committee for reviewing the abstracts and full papers and the Organising Committee for their countless effort in making the conference a success.

Alireza Behnejad, Gerard Parke and Omidali Samavati

University of Surrey, Guildford, UK, August 2021

Summary of Sessions (alphabetical order):

21st century fabrication and construction of shells (IASS WG 5)	1
Active bending	92
Advanced manufacturing (3D Printing, Digital fabrication and etc.)	165
Bamboo structures	363
Bio-based concepts inspiring the spatial structures	
and architecture of the next generation (IASS WG 12)	395
Bridge structures	668
Computational form-finding methods	709
Conceptual design	321
Conservation and preservation of 20th century historic concrete shells (IASS WG 5)10	001
Damping control and seismicity10	072
Deployable and foldable structures11	120
Design and realisation case studies: Lattice structures11	199
Design and realisation case studies: Membrane structures	290
Dynamic response of metal spatial structures (IASS WG 8)13	330
Formian in the design activity of architects and engineers15	514
Graphic statics	567
High-performance membrane buildings and challenges10	691
Historical structures	776
Inflatable structures	807
Innovative engineering	820
Life-cycle design and assessment of structures (IASS WG 18)18	859
Metal gridshell structures, connections, and stability (IASS WG 8)18	898
Morphology and configuration processing)84
Next generation parametric design (WG13)2	181
Novel micro and macro analysis and construction techniques	274
Optimisation	378
Optimisation methods for analysis and design of roof structures (IASS WG 13)24	456
Origami	658
Shell structures	766
Symmetry and spatial structures	818
Tactile strategies for teaching spatial structures (IASS WG 20)28	854
Tensegrity systems	942

Tension and membrane structures: Recent developments

in and around the United Kingdom	3001
The future of structural design - symbiosis in architecture and structural engineering	3043
The Milgo experiment	3149
Transformable structures (IASS WG 15)	
WG21: Design competition	3302
Wind engineering and CFD simulation	3402
Hangai prize lectures	3436

Contents:

21st century fabrication and construction of shells (IASS WG 5)

A mechanism for the deployment of Kinetic Umbrellas for coastal hazard adaptation1
Shengzhe WANG, Maria GARLOCK, Branko GLISIC
Some experiments on flexible formworks for shell structures
Murilo S.O. SOTO, Ruy M.O. PAULETTI, Leila C. MENEGHETTI
A path towards off-site automated fabrication of segmented concrete shells as building floors
Robin OVAL, Eduardo COSTA, Mishael NUH, Diana THOMAS-McEWEN, John ORR, Paul SHEPHERD
What future for reinforced concrete shell construction in the UK in the 21st century?
John CHILTON
Computational Design Strategies for Thin-tile Shells Manufacturing
M. Wesam Al Asali, Antiopi Koronaki, Michael H. Ramage
Dual-Purpose Concrete Shells
Alphose ZINGONI
Thin shell foundations: Historical review and future opportunities
Kiley FEICKERT, Caitlin T. MUELLER
Transverse structural behaviour of doubly curved beam-like shells
Max DOMBROWSKI, Paul MERZ, Juan P. OSMAN-LETELIER, Mike SCHLAICH

Active bending

Pattern Recognition and Prediction of Bending-active Thin Sheets via Artificial Neural Networks
Xinjie ZHOU, Xiang WANG, Dan LUO, Philip F. YUAN
Erection and shape control of a hybrid bending-active gridshell through cable activation102
Ioanna ANASTASIADOU, Marios C. PHOCAS
Hybrid formation: tension-based assembly system for bending-active plate structures
Niloofar IMANI, Axel KÖRNER, Riccardo LA MAGNA, Jan KNIPPERS
Hybrid bending active systems: a novel application of carbon fiber in lightweight structures
Maged S. GUERGUIS, Alex STILES, John-Michael WORSHAM
Grid shell sphere by the active bending weaving structure
Weixin Huang, Tepyuthyea Sophoan, Hsin-Lun Li, Ziniu Luo, Zi'an Wang, Jingyuan Hu
Lightweight curved surface system composed of bending-active plate units: A study of materials and composition

Yi-Hsuan TU, Tsung-Nan LIN

Design for manufacturing of a digital hollow section beam using interlocking connection......154

Seyed Mobin MOUSSAVI, Felix KALLWIES, Arnold WALZ, Philipp RUMPF, Stefan BÖHM, Niklas SOMMER, Stephan VÖLKERS, Julian LIENHARD

Advanced manufacturing (3D Printing, Digital fabrication and etc.)

Achieving elegant and efficient geometry in architectural frames with casting technology and advanced manufacturing: day's end project case study
Justin BINDER, Jennifer PAZDON, Richard FETUGA, Carlos DE OLIVEIRA, Bolivar VILLAMARIN
HexBox Canopy: a segmented timber plate shell with hardwood wedge joints
Christopher ROBELLER, Eduardo DE OLIVEIRA BARATA, Enrico Valentino TAGLIABOSCHI, Felix SCHMIDT- KLEESPIES
New calculation approach for selecting and orienting the reinforcing material for robotic concrete manufacturing
Abtin BAGHDADI, Robin DOERRIE, Harald KLOFT
Adaptive cross-panel system: digital fabrication for freeform architecture
Ruben AGOSTINO, Sergio PONE
Robotic construction of a self-balancing glass masonry vault: design and tessellation
Alessandro BEGHINI, Masaaki MIKI, Samantha WALKER, Isla Xi HAN, Sigrid ADRIAENSSENS, Stefana PARASCHO
Towards a multifunctional 3DCP slab system
Saqib AZIZ, Diego APELLÁNIZ, Max WEBER, Giovanni BETTI, Christoph GENGNAGEL
Rule-based generative design of translational and rotational interlocking assemblies
Pierre GILIBERT, Olivier BAVEREL, Romain MESNIL
Tailored structures – parametrics for sustainable constructions
Markus SCHEIN, Max Benjamin ESCHENBACH, Asko FROMM
Constructive design of double curved shells for 3D concrete printing
Zlata TOŠIĆ, Martin Friedrich EICHENAUER, Egor IVANIUK , Daniel LORDICK, Sonja KRASIĆ, Viktor MECHTCHERINE
Evolution of design integration with digital fabrication
Joseph BURNS
Basic research on stress deformation analysis and buckling analysis of thin chemically
tempered bent glass
Midori YUSA, Yutaka MISAWA, Takeshi ASAKAWA, Masamichi SASATANI
Repair it with additive manufacturing: an approach to the circular economy in architectural education278
Dana SAEZ, Kevin MORENO GATA, Martin TRAUTZ

Rolled-up paper spatial structure	5
Toshiaki KIMURA, Yosuke KOMIYAMA, Hiroshi TAKEYAMA, Hiroki TAKEUCHI, Yuto ISOMURA	
Robotic 3D printing with earthen materials as a novel sustainable construction method	2
Yelda GIN, Burcu Biçer SANER, Michael H. RAMAGE	
Hybrid fabrication of discrete topology optimized structures using 3D printing	12
Mauricio MORALES-BELTRAN, Kaan ÇETIN, Berk SELAMOĞLU, Halis Arda ÖZDEMIR, Fulya ÖZBEY	
Robotic construction of a self-balancing glass masonry vault: DEM study of stability during the construction stages	n 4
Vittorio PARIS, Nicola LEPORE, Edvard P.G. BRUUN, Giuseppe RUSCICA, Mario Daniele PICCIONI, Alessandro BEGHINId, Stefana PARASCHO, Sigrid ADRIAENSSENS	
All glass, compression-dominant polyhedral bridge prototype: form-finding and fabrication	26
Yao LU, Matthew CREGAN, Philipp A CHHADEH, Alireza SEYEDAHMADIAN, Mohammad BOLHASSANI, Jens SCHNEIDER, Joseph R YOST, Masoud AKBARZADEH	
Scaffold-free robotic 3D printing of a double-layer clay shell	7
Mahan MOTAMEDI, Romain MESNIL, Robin OVAL, Malo CHARIER, Olivier BAVEREL	
Multi-objective optimization of 3D printed shell toolpaths)
Alexander CURTH, Tim BRODESSER, Lawrence SASS, Caitlin MUELLER	

Bamboo structures

Creation of a pavilion with bamboo as the main material	63
Romuald SAUVERVALD, François ZANINETTI, Marie SERANTONI, Justin PONTHENIER, Elora DESREUMAU	X
Parametric simulation of bamboo structures in Mexico	71
Edwin GONZALEZ, M. Guadalupe ESTRADA, Giancarlo DI MARCO	
Development of an active bending temporary corridor based on bamboo strips: preliminary results3	83
Qiu ZHANG, Yiyi WANG, Haomin WANG, Cristoforo DEMARTINO, Francesco MARMO, Zhi LI, Yan XIAO	

Bio-based concepts inspiring the spatial structures and architecture of the next generation (IASS WG 12)

Timber elements with graded performances through digital forest to timber workflows	395
Martin TAMKE, Tom SVILANS, Sebastian GATZ, Mette RAMSGAARD THOMSEN	
Proposal of clamped joint for connecting wooden members and study of their application to spatial structures.	408
Yoshisato ESAKA, Tatsuki ISHIZAKI, Tokuma AZEMI	
The Paper Brick Vault	419
Hélène BARBIER, Théo FERRIEUX, Baptiste LACH, Kenza MAACHI, Mossaab SJAAI, Margaux	

Biobased textile reinforced concrete for the design of thin shells
Giuliana SCUDERI, Liam FLANAGAN
Geodesic winding of minimal surfaces: the architecture, structure and geometry of an irregular grid-shell pavilion assembled from thin plywood strips
Günther H. FILZ
Structural design of built-up timber beams with catenary curve shape
Takaaki UDAGAWA, Satoru NAGASE, Kenji TODA
Comparative study of bracing patterns and materials for tall timber buildings
Alexandra KAWAR, Gordana M. HERNING
Bending active plates with tensile elements: A biomimetic approach inspired by the Australian curly leaf spider (Phonognatha graeffae)
Cody TUCKER, Xiliu YANG, August LEHRECKE, Lior SKOURY, Manuela AUST, Friedrich HOLTMANN, Axel KÖRNERb, Oliver BETZ
Made by material FRUSTRATION: generation of complex morphologies through controlled geometrical incompatibilities
Arielle BLONDER, Eran SHARON
The Baya Nest pavilion project: braided pattern optimization for hanging shell structures by dynamic relaxation
Marc LEYRAL, Quentin CHEF, Sylvain EBODE, Pierre GUEROLD
Flexible and sustainable building components through kerf patterns
Ana GATÓO, Antiopi KORONAKI, M. Wesam AL ASALI, Aurimas BUKAUSKAS, Yelda GIN, Darshil U. SHAH, Eduardo WIEGAND, Michael H. RAMAGE
Utilising waste wood through reciprocal frame systems
Xan BOWNE, Olga Popovic LARSN, Caio CASTRIOTTO
An integrated architectural and structural design concept by using local, salvaged timber
Gengmu RUAN, Günther H. FILZ, Gerhard FINK
Resilient adaptive structures of multifocal asymmetric shells
Dmitri KOZLOV
Analyzing a fungal mycelium and chipped wood composite for use in construction
Dana SAEZ, Denis GRIZMANN, Martin TRAUTZ, Anett WERNER
Re-use of formwork for a villa in Amsterdam
Dr. ir. A.D.C. PRONK, R.R.L. van LOON, K.C.P. SANDERS
Material tests and execution methods of linear composite pykrete structural elements
Dr. ir. A.D.C. PRONK, M.B.G. DE BOERA, J.M. HOEF, P.M.L.M. OTTERSPOOR, L.M.J. PIELOOR, O.D. VENS

Structural design and validation of a pykrete tower through form finding
Dr. ir. A.D.C. PRONK, M.B.G. DE BOERA, J.M. VAN DE HOEF, P.M.L.M. OTTERSPOOR, L.M.J. PIELOOR, O.D. VENS
Leaf venation topologies for a ribbed floor system
Daniel REYNOLDS, Naomi FRANGOS, Eugene LEE, Gustav FAGERSTRÖM
Research in temporary, biodegradable, thin-shell, cast paper structures at full scale
Stephanie DAVIDSON
Load tests on ribbed timber shells for medium span roofs
Alexander STAHR, Christian HEIDENREICH, André KILIAN, Cristoph DIJOUX, Lukas FRANKE, Ryan HALLAHAN
Design space exploration of materially efficient CLT structures
Antiopi KORONAKI, Aurimas BUKAUSKAS, Ana GATÓO, Darshil U. SHAH, Michael H. RAMAGE
Three-dimensional fibre placement in wood for connections and reinforcements in timber structures637
Hans Jakob WAGNER, Dominga GARUFI, Tobias SCHWINN, Dylan Marx WOOD, Achim MENGES
Long-span timber gridshell design and analysis: the Taiyuan Domes
Brandon SULLIVAN, Lucas EPP, Gerald EPP
Pragmatic design and fabrication of elastic timber gridshell dwellings
Robin M. HARRISON, Mohammad BOLHASSANI

Bridge structures

Saving a space structure bridge in Mexico	668
Alejandro CALDERON-LANDAVERDE, Alejandro CALDERON-OLLIVER, Javier GONZALEZ-CANTU	
The Tide – Steel monocoque interdisciplinary digital workflow and parametric structural analysis	679
Wai PANG	
Structural design iterations of tied arch shell bridges for Toronto's waterfront revitalization	691
Matthias PELTZ, Michael STEIN, Mathias NIER, Juan PORRAL, Michael MESCHINO	
Physical modelling and design development of precast UHPC shell bridge	.700
Ahmet TOPBAS, Tarik Ateser, F. Omur TULEN, Muhammed MARASLI, Beni KOHEN	

Computational form-finding methods

A simulation process for implementation of knitted textiles in developing architectural tension structures.	709
Farzaneh OGHAZIAN, Paniz FARROKHSIAR, Felecia DAVIS	
Applications of states of self-stress to the design of gridshells	723
Alessandro BEGHINI, Max COOPER, Cameron MILLAR, William BAKER	

Isogeometric finite elements for form finding and structural analysis using particle-spring methods within Kangaroo 2
Laurin SCHÄFER, Anna M. BAUER, Philipp LÄNGST, Julian LIENHARD, Alexander MICHALSKI
A novel approach to the form finding of shells based on membrane theory744
F. MARMO, D. DI LIETO, S. GABRIELE, S. ADRIAENSSENS, M. PARADISO, L. ROSATI
Predicting the structural behavior of geometrical nonlinearity of shell structures by machine learning756
Yoshiya Moritomo, Shinnosuke Fujita
Computational hanging upside-down simulation to design axial-force-resistant stacked dome and tower structures
Hiroyuki TAGAWA, Rino TAKEUCHI
The construction of new masonry bridges inspired by Paul Séjourné
Emil ADIELS, Chris J. K. WILLIAMS
Towards trans-topological design exploration of reticulated equilibrium shell structures with graph convolution networks
Kam-Ming Mark TAM, Vahid MOOSAVI, Tom VAN MELE, Philippe BLOCK
Deep Learning Algorithm to Speed up the process of Chebyshev Gridshell Structural Optimization797
Dai KANDIL, Enrique SORIANO, Dionís BOIXADER
Advanced form-finding with design constraints and objectives through constraint projection809
Kenryo TAKAHASHI

Conceptual design

Gridshell structures with discrete curvature lines:Modelling technique and evaluation of mechanical performance.	821
Yohei YOKOSUKA, Junichi INOGUCHI, Makoto OHSAKI, Toshio HONMA	
An introduction to spatial structures for the practicing structural engineer – with case study	834
Michael O'SHEA	
Alternative conceptual design for hypar large-scale roof	846
Odine MANFRONI, Lorenzo PEDERZOLI, Stefano SILVESTRI	
Structural patterns in architecture	858
Milica D. PETROVIĆ, Isidora D. ILIĆ	
Exploring forms of masonry vaults built without centering	865
Babita NEUPANE, Rui LIU	
Re-defining arch structures through form-finding	879
Wanda J. LEWIS	

Performance of structural grids for tall buildings based on geometric Islamic patterns
Carlos MERI-CELMA, David GALLARDO, Carlos LÁZARO
Conceptual design of three-dimensional structural and sun-shading façades supported by machine- learning
Federico BERTAGNA, Pierluigi D'ACUNTO, Patrick Ole OHLBROCK
An application to generation of spatial structure using projection figures of rotated regular polyhedron based on group theory
Toshifumi MAE, Yukihiro FUJIMOTO, Yuji MATSUMOTO
Grammar-based generation of bar networks in static equilibrium with bounded bar lengths
Ioannis MIRTSOPOULOS, Corentin FIVET
Flow-informed topology design: Evaluating the conformity of structural topologies with vector fields936
Demi FANG, Caitlin MUELLER
Experimental investigation on prestressed thin-walled concrete folded slabs with CFRP textiles
María SERRANO-MESA, Juan P. OSMAN-LETELIER, Alex HÜCKLER, Mike SCHLAICH
Structure and fabrication-driven conceptual design of space-frame structures
Antiopi KORONAKI, Paul SHEPHERD, Mark EVERNDEN
On the importance of global stability for discrete gridshells created by the Thrust Network Analysis form- finding method
Sverre Magnus HAAKONSEN, June-Marie J. ESJEHOLM, Daniel May INSTANES, Steinar Hillersøy DYVIK, Anders RØNNQUIST
Postdigital ornamented architecture is not ornamented
Ghali BOUAYAD
Generative structural design for embodied carbon estimation
Ramon Elias WEBER, Caitlin MUELLER, Christoph REINHART

Conservation and preservation of 20th century historic concrete shells (IASS WG 5)
The High Life Factory: a 20th century historic concrete shell at risk of loss
Marisela MENDOZA, Juan Ignacio DEL CUETO RUIZ-FUNES
Morphological analysis of architectural work by F. Candela: the form and aperture shape of the HP shell structure
Masafumi TANAKA, Sumika INOUE
Smithfield Market: assessment of the poultry market roof1016
Christian TYGOER, James J. KINGMAN
Shrouded by time and tile: a structural investigation for preservation of Cuba's historic School of Ballet classroom and theatre domes

Damping control and seismicity

Experimental testing on semi-active vibration control through adaptive structural joints1072
Qinyu WANG, Gennaro SENATORE, Kaspar JANSENc, Arjan HABRAKEN, Patrick TEUFFEL
Design method and application of toggle brace viscous dampers in building renovation1085
Daohang HU, Xin ZHAO
Performance analysis and standardized design of base isolated modular steel structure in high seismicity area
Xin ZHAO, Gang WANG
Double damping knuckle damping system for high - rise steel structure
Xin ZHAO, Huaikun CHEN
Multi-level bi-directional evolutionary optimization for seismic design of SRC columns in super tall structure
Jinlun CAI, Xin ZHAO

Deployable and foldable structures

Experimental characterisation of the nonlinear dynamics of bistable composite shell structures1120
Christopher WILLETT, Robert DOREY, Andrew VIQUERAT
Structural parameterization of Kinetic Umbrellas under hydrostatic inundation
Shengzhe WANG, Vanessa NOTARIO, Maria GARLOCK, Branko GLISIC
Numerical characterization and optimization of the anisotropy of foldcores under shear loading1145
Fabian MUHS, Peter MIDDENDORF
Design of operable petal roofs: The case of Mercedes-Benz Stadium
Sudarshan KRISHNAN
Numerical analysis of imperfections in Miura Ori sandwich cores using isogeometric analysis1164

Design and realisation case studies: Lattice structures

The Mero legacy – inspiring space structures design
Jaime SANCHEZ-ALVAREZ, Herbert KLIMKE
Geometry and stability: design and construction of a 115m span freeform roof in Kuala Lumpur
Catherine POIRRIEZ, Yacine BOUZIDA
Design and construction of a 300m long steel and ETFE roof in Malaysia
Catherine POIRRIEZ, Yacine BOUZIDA
Long-span free-form domes
Alejandro ALGARA, Francisco CASTAÑO
Design and construction of a large-span aluminum alloy free-form latticed shell located on 11 high-rise buildings
Zhiqiang LI,Xiaowei LIU, Yuanwen OUYANG, Jian YIN, Zhenggen BI, Jian ZHOU, Qilin ZHANG
Sliding construction methods and past works of Tomoe Corporation
Yoshihiko KUROIWA, Hidekazu KONISHI
Design for production - entrance canopies for the multi-functional building of the Lakhta Center in St. Petersburg
Jaime SANCHEZ-ALVAREZ, Christian WOLKOWICZ, Kamil SCHWARNOWSKI, Mark FAHLBUSCH
Yokkaichi City Gymnasium: structural design corresponding to architectural design
Masari KAWAI, Tatsuya HANADA
Case study: Roof truss structure with large cut out and elliptic glazing surface
Zsolt NAGY, Zoltán KISS, Andrea KELEMEN, Károly BÁLINT, Annabella SÁNDULY

Design and realisation case studies: Membrane structures

Membrane roof structures of New Tochigi Stadium using PTFE membrane of different thickness......1290 EulSeok JEONG, Chikara KONISHI, Naonori HISHINUMA, Yuichi HASHIMOTO, Tomoya KOSHIO, Chikamasa OKUNO

EulSeok JEONG, Chikara KONISHI, Naonori HISHINUMA, Yuichi HASHIMOTO, Ryunosuke INOUE, Mari USUI
Damping performance of arch structure with super elastic alloy
Ken'ichi MINOWA, Kaito SHIRASAKI, Atsuyuki NAKAYA
Refurbishment of the main grandstand and roof of Sepang International Circuit Malaysia
Migico SING, Kok Keong CHOONG, Azri Hariz CHE MALID, Chong Kiat NG, Tamrin HAMZAH, Diah TALIB
Dynamic response of metal spatial structures (IASS WG 8)
Elasto-plastic seismic response behavior and evaluation of permissible deformation of single layer lattice domes designed under various loads
Tomohiko KUMAGAI , Toshiyuki OGAWA

analysis1	1341
Yuki TERAZAWA, Miho FUJISHIMA, Toru TAKEUCHI	
Structural design of sports arena with vibration control mechanism1	1353
Yoshikazu SUGIURA, Yasuyoshi HITOMI, Daisuke NISHIKAWA	
Seismic behavior factor of single-layer barrel vaults1	364
Karim ABEDI, Reza KHALILI, Mehdi POURSHA	
Seismic performance of building steel structures using equivalent linearization method1	372
Masanori FUJITA, Shoji NAKAZAWA , Shiro KATO	

Yuji TAKIUCHI, Shoji NAKAZAWA, Yuki HIGASHIYAMA, Shiro KATO

Dynamic response research of aluminum foam-filled 6082-T6 aluminum circular tube under lateral	
impact	1393

Ximei ZHAI, Lingzhao MENG, Zhaohui ZHOU

Study on equivalent static seismic force and seismic performance of arch structures	1404
Shoji NAKAZAWA, Yuji TAKIUCHI, Naoki WAKAYAMA, Yoshiki TAKASHIMA, Naoya HIGUCHI, Shiro KATO	
Influence of roof-substructure interaction on the seismic response of double-layered long-span domes1	416
Deepshikha NAIR, Toru TAKEUCHI	

Qu YANG, Liu ZHIYONG, Ma HUAIZHANG, Chen BO, Li JIAPENG, Luo YONGFENG

A new seismic damage assessment method for single-layer steel latticed shells considering multi-modal combination
Yujian ZHANG, Yongfeng LUO, Qinglong HUANG, Yang QU
Dynamic failure analysis and simplified optimization for member sections of single-layer reticulated domes under severe earthquakes
Ming ZHANG, Junjie ZHANG, Xin XIE, Alireza BEHNEJAD, Gerry PARKE
Shake-table test of a partial model of a roller-supported steel roof, Part 1: Preliminary test with steel column
Akiko KISHIDA, Jun FUJIWARA, Yuki TERAZAWA, Toru TAKEUCHI, Tetsuo YAMASHITA, Yoshinao KONISHI, Ryunosuke KISHIZAWA, Koki NISHIKAWA
Shake-table test of a partial model of a roller-supported steel roof, part 2: Test for reproducing earthquake damage
Jun FUJIWARA, Akiko KISHIDA, Yuki TERAZAWA, Toru TAKEUCHI, Koshiro NISHIMURA, Tetsuo YAMASHITA, Yoshinao KONISHI, Ryunosuke KISHIZAWA, Koki NISHIKAWA, Ryota KAJIWARA
Responsive systems in seismic computational design
Tim FISCHER, Salvatore VISCUSO, Alessandra ZANELLI
Sensitivity analysis and optimal design for vibration mitigation of large span pedestrian bridge1502
Chenyun ZHANG, Yong HUANG, Xin ZHAO

Formian in the design activity of architects and engineers

Formian in engineering and architectonic design and education
Janusz RĘBIELAK
Design and construction of reciprocal frames made of bamboo with connections by means of PVC pipe and rope
Koichiro ISHIKAWA, Sovannara SRUN, Sokol PHON
Connection orientation calculation in single-layer lattice space structures using formex algebra
Mohammad Reza CHENAGHLOU, Karim ABEDI, Hadi ESMAILNEJAD
Computational form exploration of branching columns using concepts of formex algebra and the ParaGen method
Peter VON BUELOW, Anahita KHODADADI
Data Generation for Prefabrication of Single Layer Spatial Structures
Hoshyar NOOSHIN, Omidali SAMAVATI, S. Alireza BEHNEJAD, Gerry PARKE

Graphic statics

A note on tension-compression mixed membrane shell form-finding	1567
Masaaki MIKI, Toby MITCHELL , William BAKER	

Simple rankine gridshells
Allan McROBIE, Marina KONSTANTATOU, Georgios ATHANASOPOULOS, Giancarlo TORPIANO, Cameron MILLAR, William BAKER
Lightweight structures and the geometric equilibrium in dragonfly wings
Hao ZHENG, Marton HABLICSEK, Masoud AKBARZADEH
Saving appearances: treatment of anomalies in the projective geometry-graphic statics analogy1604
Thomas E. BOOTHBY, Annalisa CRANNELL, Nathan C. BROWN
On funicular gridshells and Airy stress functions1616
Cameron MILLAR, Toby MITCHELL, Arek MAZUREK, Ashpica CHHABRA, Alessandro BEGHINI, Allan McROBIE, William F. BAKER
Application of kinematics methods in the full 3D graphic-statics description for frames
Georgios-Spyridon ATHANASOPOULOS, Allan MCROBIE
The force as a function: Towards analytical graphic statics for spatial structures
Tamás BARANYAI
On the large displacements of infinitesimal mechanisms using graphic statics
Cameron MILLAR, Allan McROBIE, William F. BAKER
Designing the geometry of auxetic baterials using graphic statics
Márton HABLICSEK, Masoud AKBARZADEH
A waste-based structure for an emergency shelter through materialization of 3D graphic statics
Amirhossein AHMADNIA, Salvatore VISCUSO, Hamed BEHMANESH, Alessandra ZANELLI
Developing a polyhedral graphic statics formulation for tetrahedral truss analysis
Salma MOZAFFARI, Márton HABLICSEK, Masoud AKBARZADEH, Thomas VOGEL

High-performance membrane buildings and challenges

Uniaxial central tearing behaviors of PVC coated fabric1	691
Xubo ZHANG, Minger WU, Han BAO	
Hysteretic behaviour in FM-FRP architectured material	702
Arielle BLONDER, Maurizio BROCATO	
Advantages of isogeometric B-Rep analysis for the parametric design of lightweight structures1	709
Ann-Kathrin GOLDBACH, Anna M. BAUER, Kai-Uwe BLETZINGER	
Sensitivity assessment of PVC coated PET woven fabrics under different weathering impacts1	1717
Hastia ASADI, Joerg UHLEMANN, Natalie STRANGHOENER, Mathias ULBRICHT	
Degradation of PVDF-coated fabrics after engineering applications with emphasis on surface microstruct mechanical properties and structural reliability index	ture, 730

Yingying SHANG, Bin YANG, Minger WU, Youji TAO, Jiaxiang QIN

Measuring the aero-elastic movement of fabric structures: An experimental approach	742
Arnaud DE COSTER, Maarten VAN CRAENENBROECK, Tine TYSMANS, Marijke MOLLAERT, Lars DE LAET	
Wrinkle-crease interaction in laminated membrane: effect of thermal loading	754
Parth K. KAMALIYA, S H UPADHYAY, H.M.Y.C. MALLIKARACHCHI	
Computational sensitivity analysis in the design process of pre-stressed lightweight structures	63
Martin FUSSEDER, Roland WÜCHNER, Kai-Uwe BLETZINGER	

Historical structures

Discerning the evolution of Candela's Shells through parametric structural analysis1	776
Edwin GONZÁLEZ, Francisco MUSTIELES, Astrid PETZOLD, Sebastián NOVOA	
Early experimentations within the masonry barrel vault1	785
Valentina BEATINI, Alessandro TASORA	
Bauersfeld's concept for the subdivision of the first built geodesic dome structure	796
Orsolya GÁSPÁR	

Inflatable structures

Inflated cushions under a moving point force1	807
Slade GELLIN, Romuald TARCZEWSKI	
Parametric study of inflatable strut for Gossamer space antenna1	814
Vikas RASTOGI, S. H. UPADHYAY, Sammir SAKHARE, Kripa. S. SINGH	

Innovative engineering

In*Tension: nets and dance	20
Sigrid ADRIAENSSENS, Tyler SPRAGUE, Janet ECHELMAN, Rebecca LAZIER	
C3 technology demonstration house: CUBE "from digital model to realisation"	27
Iurii VAKALIUK, Michael FRENZEL, Manfred CURBACH	
Innovative engineering inspired by visionary design	38
Igor G. SIOTOR, Thomas HERMEKING, Christian SCHLOEGL	
Performative porosity – adaptive infills for architectural elements	46
Mathias BERNHARD, Mohammad BOLHASSANI, Masoud AKBARZADEH	

Life-cycle design and assessment of structures (IASS WG 18)

Exploratory study on a segmented shell made of recycled-HDPE plastic	1859
Francesco LACCONE, Iason MANOLAS, Luigi MALOMO, Paolo CIGNONI	
Carbon footprint benchmarking data for shell and spatial structure buildings	871
David COLLINGS	
Fabrication-aware parametric design of segmented concrete shells	1879
Eduardo COSTA, Robin OVAL, Paul SHEPHERD, John ORR	
Computational tool for stock-constrained design of structures	1889
Jonas WARMUTH, Jan BRÜTTING, Corentin FIVET	

Metal gridshell structures, connections, and stability (IASS WG 8)

Buckling strength of latticed domes with grid-purlins and I-beams
Toru TAKEUCHI, Koichi SUMA, Yuki TERAZAWA, Masanobu IWANAGA
Progressive collapse mechanism of large-span spatial structures and prevention measures
Xianzhong ZHAO, Ruifeng LUO, Shen YAN
Experimental investigation on mechanical performance of Temcor and Box-I section hybrid gusset joints
Ying ZHANG, Xinhang ZHI, Yuanqing WANG, Zhongxing WANG, Qin ZHANG
Progressive collapse analysis of single-layer latticed domes with assembled hub joints
Ying XU, Xiaoning ZHANG, Qinghua HAN
Stability analysis of transmission line under wind load
K. ABEDI, H. SARMASTI, M.R. CHENAGHLOU
Investigation into the instability and collapse behaviour of cable-stiffened single-layer latticed barrel vaults with different forms of out-of-plane cables
Karim ABEDI, Mohammad Hossein MATINPOUR, Behzad SHEKASTEHBAND
Investigation into the stability behavior and progressive collapse of double dome double layer free form space structures
Karim ABEDI, Yavar AHMADNIA, Mohamad Reza CHENAGHLOU
Parametric design of aluminium alloy joint systems applied in a grid shell roof case
Xinye LI, Yanke TAN, Qilin ZHANG
Experimental and numerical investigation on the mechanical performance of improved aluminium alloy joint
Yanke TAN, Xinye LI, Qilin ZHANG
Modelling and experimental tests of spatial structure focused on slip joints

Maroš MOJTO, Ján BRODNIANSKÝ, Prof. Ján BRODNIANSKÝ, Jozef RECKÝ, Miroslav TILINGER
Application of buckling restrained braces for upgrading earthquake resistance of single layer grid dome
Yuji TAKIUCHI, Shiro KATO, Yoichi MUKAIYAMA, Keisuke ABE, Shoji NAKAZAWA
Experimental investigation on the stability of aluminum foam-filled 6082-T6 aluminum alloy circular tube under axial compression
Ximei ZHAI, Lingzhao MENG, Xiaoxue SHEN, Guangming CUI
New shells, new drivers
Karly BAST, Michael HOEHN, Cristobal CORREA, Craig SCHWITTER
Experimental and numerical study on compressive behavior of welded hollow spherical joints with external stiffeners
Tingting Shu, Xian Xu
Influence of edge valencies on the overall resistance of single-layer reticulated cylindrical shells2041
Ranjith KOLAKKATTIL, Konstantinos Daniel TSAVDARIDIS, Arul Jayachandran SANJEEVI
The investigation into the stability behaviour of single-layer Braced domes with bolt-column joints2053
Majid TAHERI, Mohammad Reza CHENAGHLOU, Karim ABEDI
The study on equivalent stiffness of aluminium alloy honeycomb panel-beam composite grid structure
Wang GANG, Zhao CAIQI, Ma JUN
The stability of a new single-layer combined lattice shell based on aluminium alloy honeycomb panels
Caiqi ZHAO, Jun MA, Haoyue LI, Yating WANG

Morphology and configuration processing

Finding the shape of translation surfaces and gridshells)84
Juan Gerardo OLIVA, Kevin Uriel MORALES, Gisela Fernanda CHÁVEZ	
An efficient method for design of discrete developable surfaces by Ricci flow20)96
Jingyao ZHANG, Makoto OHSAKI	
Creating novel non-periodic patterns for flat and curved surfaces from a single pentagonal element	02
Anooshe REZAEE JAVAN, Ting-Uei LEE, Yi Min XIE	
Shells of circular elements from circular meshes design	11
Alice CLUZEAU-TOMATIS, Maxime BRUNOIS	
Connection geometry evaluation in free form space structures	22
Mohammad Reza CHENAGHLOU, Karim ABEDI, Hadi ESMAILNEJAD	

Adapting computational protein folding logic for growth-based, assembly-driven spatial truss design2134
Keith J. LEE, Caitlin T. MUELLER
The Role of the sphere in the generation of Platonic solids: Greek and Chinese cross-views
S. MONNOT
Spatial structures based on solid tessellations
Vera VIANA
Curated deformation - dynamic shape change of tessellated surfaces
Mona MÜHLICH, David HORVATH, Axel KÖRNER, Riccardo LA MAGNA, Jan KNIPPERS

Next generation parametric design (WG13)

Implementation of constructability in conceptual design	2181
Katrine HØJBJERG, Poul Henning KIRKEGAARD, Valentina BEATINI	
Development of OpenSees component for Grasshopper for various types of computational morphogenesis	2194
Shinnosuke FUJITA, Makoto OHSAKI	
Immersive design of exposed and optimized structural systems	205
Mohamed A. ISMAIL, Gabriele SORRENTO, Colin DANIEL, Caitlin T. MUELLER	
Web-based, Interactive Platform for Polyhedral graphic Statics	214
Hua CHAI, Masoud AKBARZADEH	
Deep learning in early-stage structural performance prediction: assessing morphological parameters for buildings	226
Seyed Hossein ZARGAR, Nathan C. BROWN	
Holistic layout optimization of building structures	2239
Matthew GILBERT, Linwei HE	
Machine learning for human design: Sketch interface for structural morphology ideation using neural networks	249
Bryan W. X. ONG, Renaud DANHAIVE, Caitlin T. MUELLER	
Reinforcement learning for optimal topology design of 3D trusses	261
Kazuki HAYASHI, Makoto OHSAKI	

Novel micro and macro analysis and construction techniques

A novel construction method of stretching knitted metallized mesh in a deployable rib-membrane
structure
Di WIL Minger WIL Ding VIANC Thengri VAN

Di WU, Minger WU, Ping XIANG, Zhongxi YAN

Numerical and experimental verification of thin-walled sandwich facade panels	283
Martin MAGURA, Prof. Ján BRODNIANSKY	
Demolition construction technology of steel gird roof in the existing buildings based on birth and death element method.	291
Nianduo WU, Nuo XU, Zhanjun WAN, Fan SUN, Yongfeng LUO	
Application of VDC/BIM technology in Pudong Art Museum project	297
Yuken YING, Qilin ZHANG, Ran TAO, Pengfei WANG	
Approximate analysis of dense spaceframes	2307
Mehdi M. Khabbazan	
StructuralComponents 6: An early-stage design tool for flexible topologies of mid-rise concrete buildings	319
Leah DIERKER VIIK, Jeroen COENDERS, Sander PASTERKAMP	
Evaluation of concrete floor systems for embodied carbon, air-borne, and structure-borne acoustic performance	2331
Jonathan M. BROYLES, Micah R. SHEPHERD, Nathan C. BROWN	
Efficiency-based exploration of externally post-tensioned structures	343
Javier CAÑADA PÉREZ-SALA, Leonardo TODISCO	
F.A.B. Shell (Fabric – Arch – Base Shell): Concrete shell building using fabric membranes and telescopie arches as formwork	с 355
Krittika WALIA, Robin OVAL, Olivier BAVEREL	
Design method for non-sequential assembly	367
Julien GLATH, Tristan GOBINb, Romain MESNIL, Marc MIMRAM, Olivier BAVEREL	

Optimisation

Design optimization of two-way filler slabs: lightweight concrete floor systems for affordable urban construction	8
Ashley J. HARTWELL, Caitlin T. MUELLER	
Displacement-based seismic assessment of Heinz Isler's shell structures) 3
Abtin BAGHDADI, Mahmoud HERISTCHIAN, Harald KLOFT	
Parametric design of in-plane concrete dry joints by FE method and Fuzzy logic toward utilising additive manufacturing technique)5
Abtin BAGHDADI, Annahita MESHKINI, Harald KLOFT	
Application of different optimisation techniques for material minimisation of individual structural elements	7
Abtin BAGHDADI, Robin DOERRIE, Harald KLOFT	

A discrete topology optimisation method with feature size control for partial double-layer gridshell design	2430
Yongpeng HE, Paul SHEPHERD, Jie WANG	
Structural robustness analyses of concrete tall and supertall buildings	2443
Julio GARZÓN-ROCA, Karl MICALLEF, Juan SAGASETA	
Optimisation methods for analysis and design of roof structures (IASS WG 13)	
Structural shape optimization with parametric square-root functions	2456
Stavros TSERANIDIS	
Case study: optimization of envelope tertiary structure	2468
Viktoria HENRIKSSON, Nicholas MUNDELL	
Non-parametric shape design of free-form shells using extended Gauss map and discrete differential geometry	2474
Makoto OHSAKI, Kentaro HAYAKAWA	
Parametric grid mapping design tool for freeform surfaces using a genetic algorithm	2480
Lasse W. RAHBEK, Poul H. KIRKEGAARD, Umberto ALIBRANDI	
An innovative hybrid topology optimization method for truss structures based on a combination of continuous and discrete topology optimization	2492
Xianzhong ZHAO, Ruifeng LUO	
A novel triangular grid generation approach for the design of free-form grid structure	2505
Ruoqiang FENG, Fengcheng Liu	
Arch-based form finding technique in design of optimum shell structures	2513
Abtin BAGHDADI, Mahmoud HERISTCHIAN, Harald KLOFT	
Morphological research on developable free-form surface structure composed of plates	2525
Jinglan CUI, Yaozhi LUO, Makoto OHSAKI	
Optimizing support locations in structural design	2532
Ting-Uei LEE, Xianchuan MENG, Yi Min XIE	
Penn station entrance canopy - optimization with integrated design and engineering workflow	2540
Jingwen WANG, Yen-Ju Timothy TAI, Neil KATZ , Preetam BISWAS	
Shells' shape optimization based on R-Funicularity	2548
Gloria R. ARGENTO, Francesco MARMO, Valerio VARANO, Stefano GABRIELE	
Topology optimisation of gridshell structures using a density-based approach	2557
Yongpeng HE, Paul SHEPHERD, Jie WANG	
Application of a Gaussian filter to smooth optimization of free form grid shells	2568

Hiroki TAMAI
Topology optimization of multidirectional link elements for CLT shells
Ken NODA, Toshiaki KIMURA
D-Nets on rotational surfaces: equilibrium gridshell layout, symmetric to the principal stress directions
Eike SCHLING, Jonas SCHIKORE, Thomas OBERBICHLER
Simultaneous optimization of the column arrangement and shape of the shell roof using grid point coordinates
Shuichiro KOMINAMI, Shinnosuke FUJITA
Simultaneous optimization of member cross-section and brace topology to solve as a continuous problem
Keita TAKESHITA, Shinnosuke FUJITA
Simultaneous optimization of shell shape, plate thickness and topology using sigmoid function
Teppei WATANABE,Shinnosuke FUJITA
Structural optimization of latticed shells considering strain energy and collapse load factor
Taisei NISHEI, Shinnosuke FUJITA
Design method for modular shells in TRC: A combined geometrical - structural study
Arnaud DE COSTER, Marie HENNEMANN, Lars DE LAET, Tine TYSMANS
Building shells with leaning arches
Amandine CERSOSIMO, Marcin MARCH, Devon RYAN

Origami

Local rigidity analysis of rigid origami
Zeyuan HE, Simon D. GUEST
Active control of 3D printed pill-bug inspired adaptive origami
Angshuman C. BARUAH, Ann C. SYCHTERZ
Description of the origami waterbomb cell kinematics as a basis for the design of thin-walled oricrete shells
Rostislav CHUDOBA, Alice C. NIEMEYER, Homam SPARTALI, Daniel ROBERTZ, Wilhelm PLESKEN
Analysis of buckling behaviour of tubular braces based on non-rigid origami patterns
Ya ZHOU, Yuhang ZHOU, Jian FENG, Jianguo CAI
Energy absorption behaviour analysis of origami metamaterial based on self-locking mechanism
Ruijun MA, Jianguo CAI, Jian FENG

Lattice kirigami for the development of a deployable catenary arch	710
Florian LARRAMENDY, Loïs TAVERNIER	
How to use parametric curved folding design methods- a case study and comparison	720
Riccardo FOSCHI, Robby KRAFT, Rupert MALECZEK, Klara MUNDILOVA, Tomohiro TACHI	
Generating developable and rigidly foldable origami surfaces with arbitrary Gaussian curvatures27	731
Sree Chandana MADABHUSHI, Kishore Sreekumar SHENOY, Phanisri Pradeep PRATAPA	
Form generation of rigid origami by multiobjective optimization for approximating curved surface27	'43
Kentaro HAYAKAWA, Makoto OHSAKI	
Structural Characteristics of Curved Surface Composed of Tubular Origami	755
Yuya ISHIZAWA, Tomohiro TACHI	

Shell structures

Geometry optimization and laminate layup design of CFRP boom with lenticular cross section2766
Zhongxi YAN, Minger WU, Ping XIANG, Di WU
Vaults from Buildings: Thin-tile Vaulting from Stabilised Rubble Tiles
M. Wesam Al ASALI, Will HAWKINS, Michael H. RAMAGE
Assembly aware design and construction of interlocking masonry structures
Rison Prasad KARAYIL THEKKOOT, Romain MESNIL, Jean-François CARON, Olivier BAVEREL
Segmentation and assembly strategy for lamella roof shell structures
Hannes LÖSCHKE, Alexander STAHR, Tim Henrik SCHRÖDER, Felix SCHMIDT-KLEESPIES, Ryan HALLAHAN
Design and study of a fractal shell (based on dry leaf anatomy) using Lindenmayer system algorithm2808
Aman UPADHAYAY, Savita MARU

Symmetry and spatial structures

Symmetry in design and analysis of some spatial structures	.2818
Janusz RĘBIELAK	
'Quintuplet' Phenomenology of 3D Space and the Exhaustive Enumeration of 3D Symmetry Space Groups	.2828
Michael BURT	
Symmetry-generated space grids	.2840
Alphose ZINGONI	

Tactile strategies for teaching spatial structures (IASS WG 20)

Teaching lightweight and tensile structures: a pedagogy for beginning design students
Charles MACBRIDE
Learning by building: physical vs. numerical form-finding
Jelena VUKADIN, Dominik VIDOVIĆ, Josip VUCO, Elizabeta ŠAMEC, Petra GIDAK, Krešimir FRESL
Zero Gravity: radical creativity by multidisciplinary collaboration
Günther H. FILZ, Serenay ELMAS, Athanasios A. MARKOU, KatjaHÖLTTÄ-OTTO, Saurabh DEO
Visualizing structures: integrative methodology for teaching structural principles to architecture students
Maged S. GUERGUIS, Kristin K. PITTS
Elastica project: dynamic relaxation for post-formed elastic gridshells
Marc LEYRAL, Sylvain EBODE, Pierre GUEROLD, Clément BERTHOU
Designing intuitive experiences for responsive architecture
Christoph GENGNAGEL, Saqib AZIZ, Elena Francesca AMBACHER, Lukas UTZIG,, Jörg RÄDLER
A student perspective on teaching the design of shell and spatial structures through project based learning
Miriam GRAHAM, Richard HARPIN, John CARR, Paul HULBERT
Internationalisation of the Curriculum in Spatial Structures
Ramsha SALEEM, S. Alireza BEHNEJAD

Tensegrity systems

The effect of friction coefficient of the structural behavior of String Crescent Structure	42
Akira TANAKA	
Analysis of novel adaptable tensegrity towers	53
Aguinaldo FRADDOSIO, Andrea MICHELETTI, Gaetano PAVONE, Mario D. PICCIONI	
Design and analysis of deployable clustered tensegrity cable domes	64
Shuo MA, Muhao CHEN, Xingfei YUAN, Robert E. SKELTON	
A full-scale plate-based tensegrity structure as a bike parking canopy	77
Heather GATHMAN, Ann C. SYCHTERZ	
Actuation of an adaptive tensegrity-based roof structure using continuous cables	39
Sagnik PAUL, Ann C. SYCHTERZ	

Tension and membrane structures: Recent developments

Maintaining membrane structures – experiences from Ashford	
--	--

Katja BERNERT

The analytic and numerical form-finding of minimal surfaces and their application as shell structures.	3008
Alexander SEHLSTOM, Chris J. K. WILLIAMS	
X-Madrid roof	.3019
Guillermo CAPELLÁN, Santiago. GUERRA, Julio GONZÁLEZ, Javier MARTÍNEZ	
Stability of stayed columns	3029
Sudarshan KRISHNAN	
The carbon footprint of long span structures: review of the Millennium Dome and subsequent tensile systems	3033
Tim C. R. FINLAY	

The future of structural design - symbiosis in architecture and structural engineering
Geometry-based teaching of structures through computational graphic statics
Juney LEE, Lluís ENRIQUE, Tom VAN MELE, Philippe BLOCK
Teaching structures to architects – think, experience, communicate, and design
Yvonne WONG, Iori KANAO, Nachamma SOCKALINGAM, Sam C. JOYCE
Integration of parametric structural analysis and architectural design using a novel approach to enhancing timber compression members
Matthew TAM, Florian FEND, Clemens PREISINGER
Homogeneity versus heterogeneity in architect-engineer design teams
Stephanie BUNT, Nathan C. BROWN
Equilibrium without statics: The modern Müller-Breslau method
Edmond SALIKLIS
Teaching structural design to architecture students. Experiences at the Academy of Architecture in Mendrisio, Switzerland
Stefano MICCOLI, Andrea FRANGI, Roberto GUIDOTTI
Blended design studio in teaching architectural students about spatial structures
Jelena MILOŠEVIĆ
Dialogic design process: an analysis of an irregular shell with polyurethane foam
Jun CHEN
Decoding complex geometry for craftsmanship
Urvi SHETH, Shylaja REGUNATHAN
Zero Gravity: a novel cantilever beam utilizing elastic torsion for structures and architecture
Serenay ELMAS, Günther H. FILZ, Athanasios A. MARKOU, Jani ROMANOFF

The Milgo experiment

Form-making and industrial production: algorithms, Milgo experiment 1 (1997-2004)	3149
Haresh LALVANI	
Expanded surfaces: Xurf, Milgo experiment 2 (1998-2010)3	3163
Haresh LALVANI	
X-structures, Milgo experiment 3 (2008-2014)	3177
Haresh LALVANI	
Hypersurfaces, Milgo experiment 4 (2006-2012)	3190
Haresh LALVANI	

Transformable structures (IASS WG 15)

Vertex pavilion: deployable arches structure with triangular section
O. AVELLANEDA, M. MENDOZA , D. PEÑA
On the kinematics of rigid bar-linkage system typologies
Niki GEORGIOU, Marios C. PHOCAS
Geometric strategies to design a bistable deployable structure with straight scissors using flexible rods
Carlos J. GARCÍA-MORA, Jose SÁNCHEZ-SÁNCHEZ
Using flexible trapezoidal quad-surfaces for transformable design
Kiumars SHARIFMOGHADDAM, Georg NAWRATIL, Arvin RASOULZADEH, Jonas TERVOOREN
Active control and energy assessment of a prototype adaptive structure that adapts to loading through large shape changes
Arka P. REKSOWARDOJO, Gennaro SENATORE, Ian F.C. SMITH
Alignable nets: compacting elastic gridshells
Xavier TELLIER
3D Expandable origami network
Anastasia IOANNIDI, Katherine LIAPI, Vasileios SPITAS, Christos PAPALEXIS
Hybrid deployable structures consisting of miura-ori folded surfaces and translational scissors expandable frames
Evangelia VLACHAKI, Katherine A. LIAPI
Star system: A reconfigurable structure for architectural applications
Katherine A. LIAPI, Despoina KARAMPELA, Myrto LADA, Nikolaos LEVENTIS

WG21: Design competition

A study on algorithm-generated assembly of curved I and Y shaped branches for temporary shelters3302
Anton D. KEREZOV, Mikio KOSHIHARA
Designing lightweight structures from recyclable and organic materials: the rethinking lightweight pavilion
Maren ZYWIETZ, Karsten SCHLESIER, Annette BÖGLE
Knots and bars kit to construct translation gridshells
Juan Gerardo OLIVA SALINAS, Magdalena TRUJILLO BARRAGÁN
Innovative multi-culm bamboo spatial lattice structures system
Xin ZHUO, Shilin DONG
A computational framework for the design and fabrication of spatial structures with mycelium-based composites
Ali GHAZVINIAN, Arman KHALILBEIGI, Esmaeil MOTTAGHI, Benay GURSOY
WAUXI (wall auxetic installation)
Hanna M. GLETTHOFER, BA Kilian HOFFMANN, Simon WINTER
Design and analysis of moment-resisting nature-inspired-design structure using graphic statics methods
Georgios-Spyridon ATHANASOPOULOS, Timothy IRELAND, Howard GRIFFIN, Kevin SMITH, Colin CRESSER, Julien SOOSAIPILLAI, Mohammed FAWAZ, Hasin ZAHIN
The Geldeford Riband Pavillion
Dewitt GODFREY, Jeg DUDLEY, Joel HILMERSSON
A retractable roof pavilion - future and precedent
Leo Gamborg HEINZL, Valentina BEATINI, Poul Henning KIRKEGAARD

Wind engineering and CFD simulation

Aerodynamic shape optimization of helical super high-rise buildings combined with parametric modelling.	.3402
Zheng HE, Tian LIANG, Xiao LAI, Yi LU, Fan FENG, Guohui HUANG	
CFD numerical simulation of typical shape stadiums	.3413
Lei GU, Xinxin ZHANG, Hongtuo QI, Hongjun LIU, Fang WU	
The effect of design parameters on the fluid-structure interaction of hyperbolic paraboloid membrane structures.	.3425
Maarten VAN CRAENENBROECK, Marijke MOLLAERT, Lars DE LAET	

Hangai prize lectures

Adaptive framework for structural pattern optimization
Diego A. RIVERA, Renaud A. DANHAIVE, Caitlin T. MUELLER
Parametric study of non-periodic and hybrid auxetic bending-active gridshells
Yusuke SAKAI, Makoto OHSAKI
Coupled sizing, shape and topology optimisation of bistable deployable structures
Liesbeth I.W. ARNOUTS, Thierry J. MASSART, Niels DE TEMMERMAN, Péter Z. BERKE
Voss surfaces: A design space for geodesic gridshells
Nicolas MONTAGNE, Cyril DOUTHE, Xavier TELLIER, Corentin FIVET, Olivier BAVAREL
A graphical method for determining truss stability
Cameron MILLAR, Allan McROBIE, William BAKER
Self-folding rigid origami based on auxetic kirigami
Kotaro SEMPUKU, Tomohiro TACHI
Study on thermal damage of large-span ice shell structure based on thermal-mechanical coupling3508
Xiuming LIU, Yue WU, Shizhao SHEN
From ruled surfaces to elastica-ruled surfaces: New possibilities for creating architectural forms
Ting-Uei LEE, Yi Min XIE
Programmable and reconfigurable surfaces with kirigami-inspired bistable elements
Qian ZHANG, Ning PAN, Jianguo CAI, Jian FENG

Papers:



Robotic construction of a self-balancing glass masonry vault: DEM study of stability during the construction stages

Vittorio PARIS^{a*}, Nicola LEPORE^b, Edvard P.G. BRUUN^c, Giuseppe RUSCICA^a, Mario Daniele PICCIONI^b, Alessandro BEGHINI^d, Stefana PARASCHO^c, Sigrid ADRIAENSSENS^c

> * University of Bergamo, Italy vittorio.paris@unibg.it
> a University of Bergamo, Italy
> b Polytechnic University of Bari, Italy
> c Princeton University, USA
> d SOM | Skidmore, Owings & Merrill LLP

Abstract

Self-balancing construction technologies were used for centuries in the building of masonry domes and vaults. Such construction techniques were made possible through the careful design of the block tessellation and the structural form, which enabled construction of complex geometries that remain stable without falsework. These historical masonry technologies have a disruptive potential for today's construction industry when coupled with emerging innovations such as novel computational form-finding approaches and robotic fabrication. This paper presents a structural analysis of the construction stages for a doubly curved, compression-only, 2-metre-tall masonry vault inspired by traditional construction technologies and built with a cooperative human-robot fabrication process. Two ABB-IRB 6400 industrial robotic arms were precisely sequenced to alternate placing a masonry block and providing temporary support to the unfinished structure. As a result, no form- or falsework was needed during any construction stage. The paper reports an iterative procedure based on the Limit State Analysis (LSA) and Discrete Element Method (DEM) to numerically study the equilibrium of the masonry vault during all construction stages.

Keywords: Shell, vault, masonry, robotic construction, discrete element model, limit state analysis, self-balancing.

1. Introduction

Ancient master builders have built arches, vaults, and domes using masonry for millennia. These ancient forms create impressive architectural spaces that in some cases surpass the longevity of contemporary structures [1]. From the 2nd millennia BCE onwards, self-balancing construction techniques have been in use to realize many such complex structures [2]. The pitched vault [3] is perhaps the first self-balancing building system developed, which dates back to as early as the 21st century BCE [4] and is still applied in a few parts of North Africa [5]. As shown by various studies [3] [6] [7], the self-balanced state under construction is due to several factors all related with the construction work such as: the properties of building materials [6], the orientation of bed joints (as shown in figure 1) [3], and the tessellation [7].

Copyright © 2021 by the author(s) as listed above. Published in the Proceedings of the IASS Annual Symposium 2020/21 and the 7th International Conference on Spatial Structures, with permission.

Considering all of these factors, through history, several self-balancing construction technologies have also been developed [7] [8] [9], even the ones built in dry-stone masonry, widespread in the vernacular architecture of all the Mediterranean area [10]. Among all, the herringbone [11] and tile vaulting [12] constitute the most influential systems [9]. Santa Maria del Fiore's dome in Florence (1418-1436) [13] represents a notable example of the herringbone technique applied on a large scale.



Figure 1: a) The pitched vaulting technique, different scheme to lay bricks. Drawing of A. Choisy [14]. b) Revolution dome and herringbone spiralling tessellation. Drawing of F. Gurrieri [15].

As illustrated in figure 1b), the herringbone technique gets its name from its characteristic tessellation pattern: the bricks are arranged in an alternating horizontal and vertical manner [16]. Due to this tessellation and a precise sequence of laying bricks, self-supporting structural actions are formed in the dome even during its construction [17]. On the other hand, tile vaulting methods, originating in Spain around the 13rd-14th century CE [12], allows the construction of doubly-curved structures without the aid of any temporary supports through the use of fast setting gypsum mortar coupled with light tiles [18]. This technique has been a topic of recent research [6] [19] since its application to the construction of form-found vault geometries is more manageable than other self-balanced technologies. Despite specific differences in geography or time period, all the historic self-balancing masonry construction technique is being applied to. The potential of these historic technologies in the construction of complex geometries without falsework is being increasingly rediscovered in the context of emerging innovations such as novel computational form-finding approaches and robotic construction technologies.

Different approaches have been developed from the structural point of view to analyse masonry curved structures. A significant milestone toward understanding the structural behaviour of voussoir arches and vaults was made by Heyman [20], who reinterpreted the geometrical and equilibrium-based rules used by the ancient master builders through the Limit State Analysis (LSA) framework, reclaiming the power of graphic static (GS) approaches [21]. The success of this approach was due to the possibility of obtaining an accurate estimation of collapse loads using a straightforward constitutive model known as the no-tension model [22]. This model does not require the calibration of any parameters for the masonry's mechanical characterisation, which overcomes the high level of uncertainty that is usually associated with masonry structures, especially in historical constructions. More recent LSA methods based on the Thrust Line Analysis (TLA), have further reworked and extended to the analysis of complex three-dimensional structures [23] [24] [25]. In these approaches, the search for a thrust line entirely contained within the vault's thickness was extended to the three-dimensional space, as a search for discrete compression-only network or continuum unilateral membrane. Thus, according to the Safe Theorem [21], the masonry structure is stable if the thrust network [26] or surface [27] lies entirely between the intrados and the extrados surface of the vault. From a numerical point of view, literature [28] [29] [30] shows that Discrete Element Modelling (DEM) is particularly suitable to analyse the equilibrium of masonry structures. Indeed, Lemos and other researchers have proven its validity to simulate the static and dynamic behaviour of masonry structures [28] [31]. Although the potential of the

methods mentioned above to analyse complete structures is well known, evaluating the equilibrium of masonry structures under construction is scarcely explored; few works that address this, are presented in the literature [17] [32].

This paper extends the existing literature on the structural analysis of masonry structures by applying LSA and DEM methods to calculate the structural performance of a doubly-curved compression-only glass brick shell during its construction stages. The main challenge is how to investigate the vault's structural behaviour in each construction stage, while also accounting for the fact that the entire building process is carried out through a human-robot fabrication process without temporary form-or-falsework. To perform this analysis, an iterative procedure was developed that accounts for the action of the robotic arms on the structure under construction.

This research culminated in the robotic fabrication of a full-scale vault prototype at the "Anatomy of Structure" exhibit hosted at the Ambika P3 Gallery in London [33], and shown in figure 2. Different aspects of this research, from the development of the cooperative robotic fabrication strategy to the analysis of different construction sequences, are further detailed in recent works [33] [34] [35] [36].



Figure 2: Robotic fabrication of a masonry vault for the "Anatomy of Structure" exhibit.

The paper is organised as follows: section 2 describes the geometry of the vault and the material system; section 3 provides an overview on the construction process adopted and illustrates the analogies with historical self-balancing technologies; section 4 describes the methodology adopted to assess the structural state of the vault during its construction; section 5 presents the structural analysis conducted and the results; and section 6 concludes the paper and presents a discussion.

2. Vault geometry and material

The motivation for the current research comes from the exploration of ultra-light, yet efficient and strong, timbrel vault structures. This work was inspired by historical construction methods that relied on inclined courses to build vaults with the aid of only light falsework [37]. Starting from this idea, the current project was then developed with the goal of building a geometrically complex self-balancing shell without the aid of any temporary falsework. To achieve this goal, industrial robotic arms were used to both place bricks in precise complex spatial orientations and to act as temporary support to the unfinished structure [34]. As shown in figure 3, the vault has a form-found geometry, characterised by a saddle shape with a catenary profile. The span of the vault is 2.7 meters, with a length of 4.4 meters, and a rise about 2.2 meters on the outside edges and 1.9 meters for the central arch. Glass bricks were the primary elements used for the structure. As is common in masonry constructions, the geometry of

the vault had to be defined so as to minimise any tensile forces. A form-finding approach, based on the Airy's stress function [38], enabled the calculation of a doubly-curved compression-only shell. The geometry was found by an iterative process, which took into account the real distribution of the self-weight of the structure [39].



Figure 3: Geometry of the form-found shell. The central arch (red) corresponds to the first portion of the vault built. The two sides of the vault (white) are built only after completing the central arch.

Using standardised glass bricks, simplified construction by avoiding the need to field cut complex brick shapes to resolve unique geometric conditions. The material used in the joints needed to be fast-setting, rigid and with enough strength to hold the brick in place as it was placed. As reported in [34], this material was also used to compensate for the gap between different bricks courses and to deal with construction tolerances. For all these reasons, fast-setting epoxy putty [40] was selected as the joint mortar.

3. The construction phases

Two robotic arms (ABB-IRB 6400) were used to build the vault. A combination of historical technologies, such as herringbone and pitched techniques, allowed for the design of a precise construction process, with two distinct phases [34]. Phase I consists of all the construction stages related to the central arch, which was the first portion of the structure to be built. The central arch's construction is started from one side of the vault and bricks are then laid sequentially until the opposite side of the vault has been reached. The process of developing a robotic fabrication sequence that maintains stability during the construction is discussed in detail in recent works [34] [36]. Phase I ends when the last brick at the base of the arch is laid, this specific construction stage is denoted in this paper as I-h. Phase II follows phase I; here, the robot builds outward from the central arch to complete the remaining portion of the vault.

These two phases are characterised by the manner in which the two robotic arms were used. During phase **I**, the robots work cooperatively to build the central arch, one supports the incomplete arch while the second places the new glass brick. In phase **II**, the two robotic arms work separately, building two different portions of the vault; these portions are shown as the white bricks in figure 3.

This construction process incorporates several characteristics of the historical self-balancing technologies discussed in the introduction. In phase **I**, similar to the tile vaulting technique, the fast-setting property of the epoxy allows the glass bricks to maintain their position as they are laid. Meanwhile in phase **II**, the vault's tessellation is similar to the traditional herringbone technique, linking together two consecutive brick courses. Finally, the overall construction sequence is inspired by the pitched vault technology, where several consecutive self-balancing substructures are created before the full structure is completed. These substructures are shown in figure 4, where in each construction stage, **II-a**, **II-b**, **II-c**, a new arch is built.



Proceedings of the IASS Annual Symposium 2020/21 and the 7th International Conference on Spatial Structures Inspiring the Next Generation

Figure 4: Construction process for the masonry vault. a) Final stage of phase **I** and the closing of the central arch (construction stage **I-h**) b) phase **II**, where each stage is defined by the construction of a new inclined arch substructure.

4. Methodology for structural analysis

An evaluation of phase **I** was performed to assess the balanced state during construction. First a detailed TLA was carried out, dividing the central arch into individual blocks equivalent to the number of glass bricks. Thus, the equilibrium of the full structure was investigated by simulating the sequential placement of the bricks. As a result, for each construction stage related to phase **I**, an estimation of the external forces required to achieve stability was determined. These forces represent the static interaction between the structure and the robotic arms. According to LSA, no-tension material (i.e., any tensile strength provided by the epoxy putty is neglected) is adopted to perform TLA, therefore this analysis is a conservative investigation.

The epoxy putty's realistic material properties were considered in a detailed numerical analysis conducted by DEM, which was carried out for both phases in order to investigate the balanced state and

Proceedings of the IASS Annual Symposium 2020/21 and the 7th International Conference on Spatial Structures Inspiring the Next Generation

to estimate the displacements associated with each construction stage. The vault was modelled in the commercially available DEM software, 3DEC (Itasca, Minneapolis, MN, USA) [41], which allows to analyse masonry structures as a complex system of blocks [28]. These blocks can slide along their interfaces, collide or even detach [29] [30]. Through the explicit integration of Newton's laws of motion, using the finite-difference method and assuming small time-steps, the algorithm permits the evaluation of the structural behaviour of a system of bodies (either deformable or rigid) subjected to static or dynamic loads.

In the analyses performed, the vault's bricks are modelled as rigid blocks, whose size corresponds to that of the actual glass brick, which is then attached to a layer of epoxy putty surrounding it. Adopting this discretisation, the system of rigid bodies represents a good approximation of the form-found shell's structural behaviour, since the deformation is lumped at the joints. The material properties of the epoxy putty are used to model the interfaces, where a Mohr-Coulomb model with a tensile cut-off is assumed. As illustrated in figure 5, this nonlinear interface behaviour is ruled by the joint parameters: JK_n , JK_s , J_{ten} , J_{fric} and J_{coh} [42]. The JK_n , JK_s terms represent the normal and the shear stiffness of the rigid body's interfaces, respectively, while J_{ten} is the tensile strength, J_{fric} is the friction angle, and J_{coh} is the cohesive capacity. These parameters are determined based on the epoxy material's specifications [40] and verified by experiment tests, incorporating a safety coefficient.



Figure 5: Joint parameters for the rigid bodies interface (adapted from [43]).

5. Analysis and results

Both phases of construction for the masonry vault were analysed, with the purpose of verifying the selfbalancing state during the different stages. Sections, 5.1 (phase I) and 5.2 (phase II) describe the structural behaviour of the partially completed structure throughout the construction: arch behaviour is expected in phase I, and a compression-only shell behaviour in phase II

5.1. Phase I

As mentioned in section 4, TLA is executed to assess the equilibrium state of the central arch and determine the external forces that the robots must apply to guarantee this state of equilibrium. Therefore, all TLA were performed assuming that the robotic arms act as a support to the arch during construction. Although the final form-found shell was designed to achieve a fully-compressed membrane stress state, it was found that during construction the initial central arch was unable to achieve optimal structural behaviour. This is shown in figure 6a: the thrust line (red) of the central arch under construction does not entirely lie in the cross-section of initial form-found shell geometry. For this reason, the form of the complete shell had to be re-designed to ensure stability during construction.

Proceedings of the IASS Annual Symposium 2020/21 and the 7th International Conference on Spatial Structures Inspiring the Next Generation



Figure 6: TLA for central arch under construction. a) the thrust line (red) of the arch under construction falls outside of the midline of the shell geometry b) the thrust line (red) and midline of the re-designed arch coincide



Line of Thrust ----- Form-found Shell — Reaction 1 (R1) — Reaction 2 (R2)
Figure 7: Domain of orientation of the reactions R1 and R2. a) first construction stage b) last construction stage of the central arch.

According to Heyman's theory [21], and due to the modest dimensions of the structure examined, geometrical instability is the most probable cause for collapse. Therefore, investigations on the variation of minimum and maximum lines of thrust during the construction works were carried out. As reported in Figure 7a), at the first stage of construction, with only two bricks positioned, a balanced state is found if the horizontal thrust comprised in the range of 0.00-0.001kN. Despite that, the domain of orientation of the reactions, denoted by R1 and R2, is wide: about 79.5° for R1, and 54.0° for R2. This domain expresses the number of possible safe solutions that can be found, i.e., the narrower it is, the fewer number of solutions are possible. With the progress of the construction works, see figure 7b), the minimum and maximum horizontal thrust increases, to 0.09-0.10 kN, while the domain of orientation of reactions drastically narrows down to, 1.1° for R1 and 0.8° for R2.

From a numerical point of view, the robotic arm's interaction with the structure was evaluated as a kinematic constraint: the gripping points of the robotic arms allow no displacement. The first numerical simulations showed that the equilibrium state is influenced by the position of the robotic gripping point,

highlighting that an incorrectly positioned grip could lead to out-of-plane displacement. Thus, as described in [34] [36], a particular robotic sequencing construction method has been developed in order to avoid out-of-plane twisting displacement. The simulation of the construction stages conducted with DEM confirms the results obtained by TLA: the central arch reaches an equilibrium state, with the robotic arm as support, in each construction stage of phase **I**. As shown in figure 8, the arch shows a **maximum displacement of 4.27 \cdot 10^{-3} mm.**



Figure 8: Construction stages of the central arch. a) incomplete arch showing the position of the robotic support b) finished arch showing the position of control blocks (red) for the monitoring of displacements during the construction. The colour scale is associated with the displacement vectors of each node.

5.2. Phase II

The structural behaviour of phase **II** has been investigated by DEM analysis. Here, the robotic arms work separately without supporting the shell during its construction, thus, the structure is required to reach a self-balanced state at each construction stage. The numerical analysis simulated the as-built construction process for the shell. Similar to phase **I**, the structural behaviour is investigated at each construction stage; the influence on the equilibrium is established as each brick is placed.

The analysis confirms the stability of the form-found shell; furthermore, as shown in figure 9, immediately after the completion of each of the construction stages **II-a**, **II-b**, **II-c** the magnitude of the displacement decreases. As the arch substructures are completed, it allows for a redistribution of the forces, consequently, improving the structural behaviour of the partially completed structure and reducing the overall displacements. Subsequently as the construction of the next part of the structure begins, the displacements again begin to increase. This phenomenon highlights the importance of the construction sequence and the masonry tessellation, inspired by the pitched vault and herringbone technique, respectively.

The surface illustrated in figure 9, denoted by ζ , shows the variation in the magnitude of the displacements in relation to the construction stages. The surface ζ is plotted based on monitoring the behaviour of eight control points: the centroids of the blocks B_i (B₁, B₂, ..., B₈), shown in figure 8b. For example, referring to figure 9, the curve starting from B₁ in the centroid axis, expresses the variation of the magnitude of displacement recorded at the control point B₁ through each construction stage. The surface ζ displays peaks and valleys orientated in the direction perpendicular to the construction stage

axis, showing that as stages are completed the displacements decrease uniformly. The maximum displacement recorded is $4.6 \cdot 10^{-2}$ millimetres located near the intersection of the construction stage **II**-**c** and control point B₃.

The surface ζ also describes the magnitude of the residual displacement of the completed final shell (**II-d**); at this construction stage the displacement seen is lower than the maximum displacements recorded during phases **II**. The reason for this decrease is that when the structure is completed, the geometry corresponds to the final form-found shell, for which the structural behaviour has been optimised.



Figure 9: Displacement magnitudes surface (ζ). The vertical axis reports the magnitude of displacements. The other two axes represent the location of block centroids where the displacements have been recorded (B₁, B₂, B₃, ..., B₈) and the construction stages divided by the two phases I and II. Here, I-a, I-b, I-c, ..., I-h are subdivisions in phase I, while II-a, II-b and II-c are the construction stage as described in figure 4.

6. Conclusion

The potential of historical construction techniques, adopted in the context of emerging innovations in novel computational form-finding approaches and robotic construction technologies, is emphasised in the current case study. Similar to the construction of pitched vaults and herringbone vaults, factors such as, the construction process and masonry tessellation, assume primary relevance. These construction factors play a fundamental role in achieving an equilibrium state of the structure under construction. For example, in the current case, the presence of the central arch has a large influence on the stability of the construction works referenced as phase **II**, i.e., it supports the construction of the other portions of the vault, providing external reactions needed to reach an equilibrium state. Keeping this aim in mind, the knowledge of the structural state under construction is crucial; only through studies conducted in this manner can possible failures be identified. The analysis reported in sections 5.1 and 5.2 highlights the displacement and forces present in the structure under construction. TLA carried out at the end of the phase **I**, shows the existence of a narrow domain of orientation of support reactions, emphasizing that even if a balanced state could be found, a slight variation in the geometry of the arch or in the location and orientation of the supports, could lead to overturning or collapse of the shell.

Furthermore, the introduction of a temporal variable in the structural analysis allows mapping of variations in the structural behaviour throughout the construction process. As illustrated in section 5.2,

the study of the surface ζ , shows the variation in the structural behaviour between phases I and II. In phase I, the balanced state can be reached only by arch behaviour, here, the surface ζ is regular and the maximum displacement recorded in the central arch is significantly lower than that of phase II, where the rest of the vault is constructed, and a compressed membrane behaviour occurs. In phase II, the surface ζ is described by peaks and valleys. Between the construction stage I-h and II-a, ζ shows a strong variation: the magnitude of displacement of all blocks of the central arch increases by an order, defining the first peak that corresponds to II-a. This temporal interval (between I-h and II-a) starts when the central arch is completed and ends when the substructure corresponding to the second arch is closed. Immediately after its completion (after II-a), a new and more stable structure exhibiting compressionshell behaviour occurs. With this altered structural behaviour, the magnitude of displacements decreases, which coincides with the first valley in ζ , as seen in figure 9. Further, the valleys correspond to construction stages which follow the completion of arch substructures, and where redistribution of forces occurs leading to a more stable shell behaviour. This phenomenon is even more evident at the completed vault stage (end of II-d), where the pure compression shell behaves as designed.

The paper originates from a study of the historical construction technologies. The analysis and the discussion reported here are extremely relevant to the field of contemporary self-balancing technologies and ultimately for the task of construction cost-optimisation. Only by considering the state of the structure during construction works, is it possible to assess the self-balanced state and thus, drastically decrease the material cost of construction [44]. Recent works [45] [46] have shown potential in this direction, using cooperative robotics and other non-traditional fabrication systems to build complex structures without formwork. These developments have the potential to impact the building industry, but first require a better framework for evaluating a structure's behaviour during all phases of construction. As research [17] also shows, this investigation is one of the first bricks placed along the path towards establishing such an analysis-framework.

Acknowledgements

The authors want to express their gratitude for providing 3DEC software under the Education Partnership Program. We would also like to acknowledge the Metropolis Project of Princeton University, and the Princeton Catalysis Initiative for financially supporting this project.

References

- [1] I. Papayianni, 'The longevity of old mortars', *Appl. Phys. A*, vol. 83, no. 4, pp. 685–688, Jun. 2006.
- [2] S. El-Naggar, 'Les voûtes dans l'architecture de l'Égypte ancienne', *Inst. Fr. Archéologie Orient.*, vol. 1, 1999.
- [3] G. w. Van Beek, 'Arches and Vaults in the Ancient Near East', *Sci. Am.*, vol. 257, no. 1, pp. 96–103, 1987.
- [4] R. Besenval, *Technologie de la voûte dans l'orient ancien*, vol. 1, 2 vols. Paris: Editions Recherche sur les civilisations, 1984.
- [5] P. Block, M. DeJong, L. Davis, and J. Ochsendorf, 'Tile vaulted systems for low-cost construction in Africa', vol. 7, no. 1, p. 10, 2010.
- [6] L. Davis, M. Rippmann, and T. Pawlofsky, 'Innovative funicular tile vaulting: A prototype vault in Switzerland', p. 12, 2012.
- [7] G. Conti, 'La spinapesce nel Rinascimento tra Filippo Brunelleschi, i Sangallo e Bernardo Buontale nella Grotta Grande del Giardino di Boboli : alcune considerazioni matematiche', Spinapesce Nel Rinascim. Tra Filippo Brunelleschi Sangallo E Bernardo Buontale Nella Grotta Gd. Giard. Boboli Alcune Considerazioni Mat., pp. 246–254, 2013.
- [8] S. Huerta, 'The geometry and construction of Byzantine vaults: the fundamental contribution of Auguste Choisy', in *Auguste Choisy (1841-1909). L'architecture et l'art de bâtir*, Madrid, Jan.

2009, pp. 289-305.

- [9] J. Ochsendorf, *Guastavino Vaulting: The Art of Structural Tile*. Princeton Architectural Press, 2014.
- [10] A. Fraddosio, N. Lepore, and M. D. Piccioni, 'Further refinement of the Corbelling Theory for the equilibrium analysis of corbelled domes', *Curved Layer. Struct.*, vol. 6, no. 1, pp. 30–40, Mar. 2019.
- [11] S. di Pasquale, P. L. Badini, and G. Tempesta, *Rappresentazione analitica e grafica della cupola di Santa Maria del Fiore*. Firenze: Cooperativa Libraria Universitatis Studii Fiorentini Via S. Gallo, 25 Firenze, 1977.
- [12] A. Almagro, *Bóvedas tabicadas en la Cartuja de Granada: el final de un proceso evolutivo*. Universidad Politécnica de Valencia, 2012.
- [13] A. Pizzigoni, Brunelleschi, I. Bologna: Zanichelli, 1989.
- [14] A. Choisy, *Histoire de l'architecture.*, 1st ed., vol. 1, 2 vols. Paris: Gauthier-Villars, Imprimeur-Libraire du Bureau des Longitudes, de l'École Polytechnique, 1899.
- [15] F. Gurrieri, La cupola del Brunelleschi. Firenze: Accademia dell'Iris, 2010.
- [16] A. Pizzigoni, V. Paris, M. Pasta, M. Morandi, and A. Parsani, 'Herringbone naked structure', *Proc. IASS Annu. Symp.*, vol. 2018, no. 12, pp. 1–6, Jul. 2018.
- [17] V. Paris, A. Pizzigoni, and S. Adriaenssens, 'Statics of self-balancing masonry domes constructed with a cross-herringbone spiraling pattern', *Eng. Struct.*, vol. 215, p. 110440, Jul. 2020.
- [18] J. Ochsendorf, 'Tile Vaulting Innovations by Rafael Guastavino Jr. and Eduardo Torroja', J. Int. Assoc. Shell Spat. Struct., vol. 61, no. 1, pp. 59–66, Mar. 2020.
- [19] D. L. López, T. V. Mele, and P. Block, 'The combination of tile vaults with reinforcement and concrete', *Int. J. Archit. Herit.*, vol. 13, no. 6, pp. 782–798, Aug. 2019.
- [20] J. Heyman, 'On shell solutions for masonry domes', Int. J. Solids Struct., vol. 3, no. 2, pp. 227–241, Mar. 1967.
- [21] J. Heyman, 'The stone skeleton', Int. J. Solids Struct., vol. 2, no. 2, pp. 249–279, Apr. 1966.
- [22] M. Angelillo, P. B. Lourenço, and G. Milani, 'Masonry behaviour and modelling', in *Mechanics* of Masonry Structures, M. Angelillo, Ed. Vienna: Springer, 2014, pp. 1–26.
- [23] P. Block, M. DeJong, and J. Ochsendorf, 'As Hangs the Flexible Line: Equilibrium of Masonry Arches', *Nexus Netw. J.*, vol. 8, no. 2, pp. 13–24, Oct. 2006.
- [24] L. Davis and P. Block, 'Earthen Masonry Vaulting: Technologies and Technology Transfer', in Building Ethiopia: Sustainability and Innovation in Architecture and Design, Vol. I, Ethiopian Institute of Architecture, Building Construction and City Development, 2012, pp. 219–233.
- [25] E. De Chiara, C. Cennamo, A. Gesualdo, A. Montanino, C. Olivieri, and A. Fortunato, 'Automatic generation of statically admissible stress fields in masonry vaults', *J. Mech. Mater. Struct.*, vol. 14, no. 5, pp. 719–737, Dec. 2019.
- [26] P. Block and J. Ochsendorf, 'Thrust Network Analysis: A New Methodology for Three-Dimensional Equilibrium', J. Int. Assoc. Shell Spat. Struct., vol. 48, no. 3, pp. 167–173, Dec. 2007.
- [27] A. Fraddosio, N. Lepore, and M. D. Piccioni, 'Thrust Surface Method: An innovative approach for the three-dimensional lower bound Limit Analysis of masonry vaults', *Eng. Struct.*, vol. 202, p. 109846, Jan. 2020.
- [28] S. Vasilis, B. Katalin, L. V José, and M. Gabriele, *Computational Modeling of Masonry Structures Using the Discrete Element Method*. IGI Global, 2016.
- [29] P. A. Cundall, 'Formulation of a three-dimensional distinct element model—Part I. A scheme to detect and represent contacts in a system composed of many polyhedral blocks', *Int. J. Rock Mech. Min. Sci. Geomech. Abstr.*, vol. 25, no. 3, pp. 107–116, Jun. 1988.
- [30] R. Hart, P. A. Cundall, and J. Lemos, 'Formulation of a three-dimensional distinct element model—Part II. Mechanical calculations for motion and interaction of a system composed of many polyhedral blocks', *Int. J. Rock Mech. Min. Sci. Geomech. Abstr.*, vol. 25, no. 3, pp. 117–

125, Jun. 1988.

- [31] D. L. Fang, R. K. Napolitano, T. L. Michiels, and S. M. Adriaenssens, 'Assessing the stability of unreinforced masonry arches and vaults: a comparison of analytical and numerical strategies', *Int. J. Archit. Herit.*, vol. 13, no. 5, pp. 648–662, Jul. 2019.
- [32] I. J. Oppenheim, D. J. Gunaratnam, and R. H. Allen, 'Limit State Analysis of Masonry Domes', *J. Struct. Eng.*, vol. 115, no. 4, pp. 868–882, Apr. 1989.
- [33] I. X. Han, E. P. G. Bruun, S. Marsh, M. Tavano, S. Adriaenssens, and S. Parascho, 'From Concept to Construction: A Transferable Design and Robotic Fabrication Method for a Building-Scale Vault', in *Proceedings of the 40th Annual Conference of the Association for Computer Aided Design in Architecture*, 2020, pp. 1–12. (To appear)
- [34] S. Parascho, I. X. Han, S. Walker, A. Beghini, E. P. G. Bruun, and S. Adriaenssens, 'Robotic vault: a cooperative robotic assembly method for brick vault construction', *Constr. Robot.*, vol. 4, no. 3, pp. 117–126, Dec. 2020.
- [35] S. Parascho, I. X. Han, A. Beghini, M. Mike, E. P. G. Bruun, and S. Adriaenssens, 'LightVault: A Design and Robotic Fabrication Method for Complex Masonry Structures', Paris (France), 2021. (To appear)
- [36] E. P. G. Bruun *et al.*, 'Three Cooperative Robotic Fabrication Methods for the Scaffold-Free Construction of a Masonry Arch', 2021, eprint: 2104.04856.
- [37] SOM, 'Bricks, Mortar, and Robots: Solutions for Sustainable Construction', *Medium*, Aug. 22, 2019. https://som.medium.com/bricks-mortar-and-robots-solutions-for-sustainable-construction-f404b90fe9ab (accessed Apr. 09, 2021).
- [38] M. Masaaki, I. Takeo, and B. Philippe, 'Parametric Self-supporting Surfaces via Direct Computation of Airy Stress Functions', *ACM Trans. Graph. TOG*, pp. 1–12, 2015.
- [39] M. Miki, E. Adiels, W. Baker, T. Mitchell, A. Sehlstrom, and C. Williams, 'Form-Finding of Shells Containing Both Tension and Compression Using the Airy Stress Function', Dec. 2020.
- [40] 'Oatey, R Fix-ItTM Stick Epoxy Putty'. 2020, [Online]. Available: URL https://www.oatey.com/products/oatey-fixit-stick- epoxy-putty-1829259701.
- [41] 3DEC / US Minneapolis Itasca Consulting Group, Inc. .
- [42] Manual, Theory and Background. Minneapolis: Itasca Consulting Group. Inc, 2016.
- [43] E. Çaktı, Ö. Saygılı, J. V. Lemos, and C. S. Oliveira, 'Discrete element modeling of a scaled masonry structure and its validation', *Eng. Struct.*, vol. 126, pp. 224–236, Nov. 2016
- [44] F. Barbosa *et al.*, 'Reinventing Construction: A Route to Higher Productivity', McKinsey Global Institute, 2017. Accessed: Mar. 25, 2021. [Online].
- [45] E. P. G. Bruun, I. Ting, S. Adriaenssens, and S. Parascho, 'Human–robot collaboration: a fabrication framework for the sequential design and construction of unplanned spatial structures', *Digit. Creat.*, pp. 1–17, Nov. 2020..
- [46] P. Latteur, S. Goessens, and C. Mueller, 'Masonry construction with drones', *Proc. IASS Annu. Symp.*, vol. 2016, no. 7, pp. 1–10, Sep. 2016.



SSRC@surrey.ac.uk

Spatial Structures Research Centre, Department of Civil and Environmental Engineering, University of Surrey



The Spatial Structures Research Centre (SSRC) of the University of Surrey was founded by Professor Zygmunt Stanislaw Makowski in the Department of Civil and Environmental Engineering in 1963. The core aim of SSRC has been conducting research in the design, analysis and construction of spatial structures. Also, education of spatial structures has been at the centre of its ethos over the past six decades. Many different activities have been organised by the Centre over these almost 60 years, in areas such as research, publication, teaching, organisation of conferences, as well as, consulting work.



ISBN 978-1-7399393-3-5

